



266 Tapped Full Circle® Repair Clamp

Double Band

All Stainless Steel



Smith-Blair® 266 Double Band Tapped Full Circle® All Stainless Steel Repair Clamps offer the advantage of greater size range over single band clamps. Each clamp has the capability to fit a wide variety of types and classes of pipe within a nominal pipe size, thus reducing stock requirements. The clamps are also able to repair damaged or broken service connections or branch lines. Repairs can be made and service connections or branch lines restored in one operation. They can also be used for new installations of service connections or branch lines and are designed for use on pipe from 4" to 12" nominal size.

Band Width Inches	Number of Studs	Stud Sizes
7 1/2	4	5/8" x 7"
12 1/2	6	

Material Specifications	
Band:	Stainless Steel Type 304
Lugs:	Stainless Steel Type 304
Keeper Bars:	Stainless Steel Type 304
Gasket:	Nitrile (Buna N). Specially compounded to resist oil, acids alkalies, most (aliphatic) hydrocarbon fluids, water and many chemicals. Nominal temperature range from -20°F to 180°F. Consult manufacturer for specific applications or other service temperatures.
Bridge Plate:	Stainless Steel recessed flush and bonded into gasket.
Stud Bolts:	Stainless Steel Type 304, coated to prevent galling
Nuts:	Stainless Steel Type 304 fluoropolymer coated nuts to prevent galling.

Material specifications are subject to change.

3/4" and 1" NPT Taps

Standard				Catalog Number		Metric			
Nom. Size Inches	O.D. Range Inches	Width Inches	Wt. Each Lbs.	Catalog Number		Nom. Size MM	O.D. Range MM	Width MM	Wt. Each Kg.
				3/4" NPT/20 MM	1" NPT/25 MM				
4	4.44-5.25	7 1/2 12 1/2	9.9 16.2	266-20045007-006	266-20045007-008	100	113-133	190 317	4.5 7.4
				266-20045012-006	266-20045012-008				
6	6.62-7.42	7 1/2 12 1/2	11.3 18.5	266-20066307-006	266-20066307-008	150	168-189	190 317	5.1 8.4
				266-20066312-006	266-20066312-008				
6	6.84-7.64	7 1/2 12 1/2	11.4 18.7	266-20069007-006	266-20069007-008	150	174-194	190 317	5.2 8.5
				266-20069012-006	266-20069012-008				
8	8.62-9.42	7 1/2 12 1/2	13.0 21.3	266-20086307-006	266-20086307-008	200	219-239	190 317	5.9 9.7
				266-20086312-006	266-20086312-008				
8	8.99-9.79	7 1/2 12 1/2	13.6 22.3	266-20090507-006	266-20090512-008	200	229-248	190 317	6.2 10.1
				266-20090512-006	266-20090512-008				
10	10.75-11.55	12 1/2	26.4	266-20107512-006	266-20107512-008	250	273-293	317	12
10	11.10-11.90	12 1/2	26.7	266-20111012-006	266-20111012-008	250	282-302	317	12.1
12	12.75-13.55	12 1/2	29.3	266-20127512-006	266-20127512-008	300	324-344	317	13.3
12	13.20-14.00	12 1/2	29.5	266-20132012-006	266-20132012-008	300	335-355	317	13.4

1 1/4", 1 1/2" and 2" NPT Taps

Standard				Catalog Number			Metric			
Nom. Size Inches	O.D. Range Inches	Width Inches	Wt. Each Lbs.	Catalog Number			Nom. Size MM	O.D. Range MM	Width MM	Wt. Each Kg.
				1 1/4" NPT/32 MM	1 1/2" NPT/40MM	2" NPT/50 MM				
4	4.44-5.25	7 1/2 12 1/2	9.9 16.2	266-20045007-010	266-20045007-012	-	100	113-133	190 317	4.5 7.4
				266-20045012-010	266-20045012-012	-				
6	6.62-7.42	7 1/2 12 1/2	11.3 18.5	266-20066307-010	266-20066307-012	-	150	168-189	190 317	5.1 8.4
				266-20066312-010	266-20066312-012	266-20066312-014				
6	6.84-7.64	7 1/2 12 1/2	11.4 18.7	266-20069007-010	266-20069007-012	-	150	174-194	190 317	5.2 8.5
				266-20069012-010	266-20069012-012	266-20069012-014				
8	8.62-9.42	7 1/2 12 1/2	13.0 21.3	226-20086307-010	226-20086307-012	-	200	219-239	190 317	5.9 9.7
				266-20086312-010	266-20086312-012	266-20086312-014				
8	8.99-9.79	7 1/2 12 1/2	13.6 22.3	266-20090507-010	266-20090507-012	-	200	229-248	190 317	6.2 10.1
				266-20090512-010	266-20090512-012	266-20090512-014				
10	10.75-11.55	12 1/2	26.4	266-20107512-010	266-20107512-012	266-20107512-014	250	273-293	317	12
10	11.10-11.90	12 1/2	26.7	266-20111012-010	266-20111012-012	266-20111012-014	250	282-302	317	12.1
12	12.75-13.55	12 1/2	29.3	266-20127512-010	266-20127512-012	266-20127512-014	300	324-344	317	13.3
12	13.20-14.00	12 1/2	29.5	266-20132012-010	266-20132012-012	266-20132012-014	300	335-355	317	13.4

Other Full Circle® Clamps are available with tapped outlets.

NOTE: NOT recommended for PE pipe applications.