



EB Style Pipe Line Caps for Steel Pipe Sizes, Alloy Bolts and Nuts

Made with blind end flange
Vented (1" NPT Fem.)

PIPE		Catalog Number	M. RING Thickness & Length	BOLTS		LIST PRICE				Wt. Each Lbs.
Nom. Size Inches	O.D. Inches			No.	Size	Shop Coat		Epoxy Coated		
						Plain	Conductive	Plain	Conductive	
+ 1 1/4	1.660	EB1V	.134x5	2	1/2x7	\$51.17	\$52.26	\$53.38	\$59.72	4.0
2	2.375	EB2V	.156x5	3	5/8x9	115.91	121.34	122.97	145.12	11.0
3	3.500	EB3V	.203x5	4	5/8x9	147.30	156.56	173.42	193.72	16.0
4	4.500	EB4V	.203x5	4	5/8x9	171.36	182.59	201.81	225.92	18.0
6	6.625	EB6V	.250x5	6	5/8x9	255.00	265.50	300.25	328.29	30.0
8	8.625	EB8V	.250x5	6	5/8x9	280.36	333.18	328.99	361.92	36.0
10	10.750	EB10V	.250x5	8	5/8x9	400.29	425.14	427.01	503.24	60.0
12	12.750	EB12V	.250x5	8	5/8x9	451.21	480.94	493.83	589.18	72.0

+Nitrile (Buna N) Gasket

For Epoxy Coating, add "S" to end of Catalog Number.

For Plain Gaskets, add "P" to end of Catalog Number.

For Bonding Gaskets, add "B" to end of Catalog Number.

When ordering, please specify size, catalog number and gasket type.

FOR SEALING PURPOSES ONLY. Where pipe pullout might occur, use Maxi-Grip™ Restraint Couplings or Rod and Lug Harness Device.

EB Style Pipe Line Caps for Steel Pipe Sizes, Bond SBR Gasket and Alloy Bolts and Nuts

PIPE		Catalog Number	M. RING Thickness & Length	BOLTS		LIST PRICE		Wt. Ea. Lbs.
Nom. Size Inches	O.D. Inches			No.	Size	Shop Coat (B)	Epoxy Coated (SB)	
14	14.000	EB14.0BV	.375x7	10	5/8x9	\$734.33	\$764.83	75.0
16	16.000	EB16.0BV	.375x7	10	5/8x9	764.26	801.38	97.0
18	18.000	EB18.0BV	.375x7	12	5/8x9	932.21	982.69	113.0
20	20.000	EB20.0BV	.375x7	12	5/8x9	1,259.62	1,338.86	140.0
22	22.000	EB22.0BV	.375x7	16	5/8x9	1,285.78	1,447.40	140.0
24	24.000	EB24.0BV	.375x7	16	5/8x9	1,333.18	1,456.13	153.0

150 PSI working pressure, other ratings available.

Larger sizes and different vent sizes available.

All caps are supplied with plugs.

Thrust Blocks are required when the line is tested or placed in use.

FOR SEALING PURPOSES ONLY. Where pipe pullout might occur, use Maxi-Grip™ Restraint Couplings or Rod and Lug Harness Device.