



Maxi-Grip™ EZ® Class III Couplings

Seal and Restraint - Insulating on Cast Iron End

Cast Iron Reducing to IPS Steel or Plastic Pipe

| PIPE REDUCTION | | | | Catalog Number | M. RING Thickness & Length | BOLTS | | LIST PRICE Other Gasket Conductive | Wt. Each Lbs. |
|----------------|-------|--------|-------|----------------|----------------------------------|-------|----------------|--|---------------------|
| NOMINAL | | ACTUAL | | | | No. | Size Inches | | |
| CI | IPS | CI | IPS | | | | | | |
| 2 | 1 1/4 | 2.50 | 1.660 | EZ25169A7UMG | .120x7 | 3 | 5/8x12 | \$260.49 | 14.0 |
| 2 | 2 | 2.50 | 2.375 | EZ25239A7UMG | .156x7 | 3 | 5/8x12 | 275.70 | 14.0 |
| 2 1/4 | 1 1/4 | 2.75 | 1.660 | EZ27169A7UMG | .120x7 | 3 | 5/8x12 | 260.49 | 14.0 |
| 2 1/4 | 2 | 2.75 | 2.375 | EZ27239A7UMG | .156x7 | 3 | 5/8x12 | 275.70 | 14.0 |
| 3 | 2 | 3.80 | 2.375 | EZ38239A7UMG | .156x7 | 4 | 5/8x12 | 300.47 | 19.0 |
| 3 | 3 | 3.80 | 3.500 | EZ38359A7UMG | .203x7 | 4 | 5/8x12 | 312.56 | 19.0 |
| 4 | 2 | 4.80 | 2.375 | EZ48239A7UMG | .156x7 | 4 | 5/8x12 | 388.94 | 23.0 |
| 4 | 3 | 4.80 | 3.500 | EZ48359A7UMG | .156x7 | 4 | 5/8x12 | 382.49 | 23.0 |
| 4 | 4 | 4.80 | 4.500 | EZ48459A7UMG | .203x7 | 4 | 5/8x12 | 350.16 | 23.0 |
| 6 | 4 | 6.90 | 4.500 | EZ69459A7UMG | .188x7 | 6 | 5/8x12 | 567.16 | 50.0 |
| 6 | 6 | 6.90 | 6.625 | EZ69669A7UMG | .250x7 | 6 | 5/8x12 | 508.94 | 43.0 |
| 6 O.S. | 4 | 7.10 | 4.500 | EZ71459A7UMG | .188x7 | 6 | 5/8x12 | 650.10 | 50.0 |
| 6 O.S. | 6 | 7.10 | 6.625 | EZ71669A7UMG | .250x7 | 6 | 5/8x12 | 608.17 | 43.0 |
| 8 | 6 | 9.05 | 6.625 | EZ90669A7UMG | .250x7 | 8 | 5/8x12 | 1,019.08 | 62.0 |
| 8 | 8 | 9.05 | 8.625 | EZ90869A7UMG | .250x7 | 8 | 5/8x12 | 968.82 | 56.0 |

When ordering, please specify size and catalog number.
All Maxi-Grip™ Couplings are Epoxy Coated.